

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	
				PE	STC	LTC	BTC	STC	LTC	BTC				API	SD
13.375	48.00	H-40	740	1730	1730		1730	322		607	541	0.330	12.715	12.559	
13.375	54.50	J-55	1130	2730	2730		2730	514		909	853	0.380	12.615	12.459	
13.375	54.50	K-55	1130	2730	2730		2730	547		1038	853	0.380	12.615	12.459	
13.375	54.50	HCK-55	1400	2730	2730		2730	689		1194	853	0.380	12.615	12.459	
13.375	61.00	J-55	1540	3090	3090		3090	595		1025	962	0.430	12.515	12.359	
13.375	61.00	K-55	1540	3090	3090		3090	633		1169	962	0.430	12.515	12.359	
13.375	61.00	HCK-55	2040	3090	3090		3090	798		1345	962	0.430	12.515	12.359	
13.375	68.00	J-55	1950	3450	3450		3450	675		1140	1069	0.480	12.415	12.259	
13.375	68.00	K-55	1950	3450	3450		3450	718		1300	1069	0.480	12.415	12.259	
13.375	68.00	HCK-55	2850	3450	3450		3450	905		1496	1069	0.480	12.415	12.259	
13.375	68.00	L-80	2260	5020	5020		5020	952		1545	1556	0.480	12.415	12.259	
13.375	68.00	HCL-80	2910	5020	5020		5020	1093		1732	1556	0.480	12.415	12.259	
13.375	68.00	N-80	2260	5020	5020		5020	963		1585	1556	0.480	12.415	12.259	
13.375	68.00	HCN-80	2910	5020	5020		5020	1103		1732	1556	0.480	12.415	12.259	
13.375	68.00	C-90	2320	5650	5650		5650	1057		1683	1750	0.480	12.415	12.259	
13.375	68.00	S-95	2910	5970	5970		5970	1125		1812	1847	0.480	12.415	12.259	
13.375	68.00	T-95	2330	5970	5970		5970	1114		1772	1847	0.480	12.415	12.259	
13.375	68.00	C-95	2330	5970	5970		5970	1114		1772	1847	0.480	12.415	12.259	
13.375	68.00	HCP-110	2910	6910	6910		6910	1297		2079	2139	0.480	12.415	12.259	
13.375	68.00	P-110	2340	6910	6910		6910	1297		2079	2139	0.480	12.415	12.259	
13.375	72.00	L-80	2670	5380	5380		5380	1029		1650	1661	0.514	12.347	12.191	12.250
13.375	72.00	HCL-80	3470	5380	5380		5380	1181		1850	1661	0.514	12.347	12.191	12.250
13.375	72.00	N-80	2670	5380	5380		5380	1040		1693	1661	0.514	12.347	12.191	12.250
13.375	72.00	HCN-80	3470	5380	5380		5380	1192		1850	1661	0.514	12.347	12.191	12.250
13.375	72.00	C-90	2780	6050	6050		6050	1142		1798	1869	0.514	12.347	12.191	12.250
13.375	72.00	H2S-90	3470	6050	6050		6050	1192		1850	1869	0.514	12.347	12.191	12.250
13.375	72.00	S-95	3470	6390	6390		6390	1215		1935	1973	0.514	12.347	12.191	12.250
13.375	72.00	T-95	2820	6390	6390		6390	1204		1893	1973	0.514	12.347	12.191	12.250
13.375	72.00	H2S-95	3470	6390	6390		6390	1204		1893	1973	0.514	12.347	12.191	12.250
13.375	72.00	C-95	2820	6390	6390		6390	1204		1893	1973	0.514	12.347	12.191	12.250
13.375	72.00	HCP-110	3470	7400	7400		7400	1402		2221	2284	0.514	12.347	12.191	12.250
13.375	72.00	P-110	2890	7400	7400		7400	1402		2221	2284	0.514	12.347	12.191	12.250
13.375	72.00	HCQ-125	3470	8410	8410		8410	1577		2463	2596	0.514	12.347	12.191	12.250
13.375	72.00	Q-125	2880	8410	8410		8410	1577		2463	2596	0.514	12.347	12.191	12.250
13.375	72.00	V-150	2880	10090	10090		10090	1887		2939	3115	0.514	12.347	12.191	12.250
13.375	80.70	H2S-90	4990	6830			7340			2077	2098	0.580	12.215	12.059	
13.375	80.70	S-95	4990	7210			7210			2173	2215	0.580	12.215	12.059	
13.375	80.70	H2S-95	4990	7210			7210			2125	2215	0.580	12.215	12.059	
13.375	80.70	HCP-110	4990	8350			8350			2493	2565	0.580	12.215	12.059	
13.375	80.70	P-110	4000	8350			8350			2493	2565	0.580	12.215	12.059	
13.375	80.70	HCQ-125	4990	9490			9490			2765	2914	0.580	12.215	12.059	

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	
				PE	STC	LTC	BTC	STC	LTC	BTC				API	SD
13.375	80.70	Q-125	4140	9490			9490			2765	2914	0.580	12.215	12.059	
13.375	86.00	S-95	6240	7770			7750			2333	2378	0.625	12.125	11.969	
13.375	86.00	HCP-110	6240	9000			8980			2677	2754	0.625	12.125	11.969	
13.375	86.00	P-110	4780	9000			8980			2677	2754	0.625	12.125	11.969	
13.375	86.00	HCQ-125	6240	10220			10200			2969	3129	0.625	12.125	11.969	
13.375	86.00	Q-125	5030	10220			10200			2969	3129	0.625	12.125	11.969	