

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	
				PE	STC	LTC	BTC	STC	LTC	BTC				API	SD
16.000	65.00	H-40	630	1640	1640		1640	439		781	736	0.375	15.250	15.062	
16.000	75.00	J-55	1020	2630	2630		2630	710		1200	1178	0.438	15.124	14.936	
16.000	75.00	K-55	1020	2630	2630		2630	752		1331	1178	0.438	15.124	14.936	
16.000	84.00	J-55	1410	2980	2980		2980	817		1351	1326	0.495	15.010	14.822	
16.000	84.00	K-55	1410	2980	2980		2980	865		1499	1326	0.495	15.010	14.822	
16.000	84.00	N-80	1480	4330	4330		4330	1167		1898	1929	0.495	15.010	14.822	
16.000	84.00	HCN-80	1910	4330	4330		4330	1342		1898	1929	0.495	15.010	14.822	
16.000	84.00	HCP-110	1910	5960	5960		5960	1575		2518	2652	0.495	15.010	14.822	
16.000	84.00	P-110	1480	5960	5960		5960	1575		2518	2652	0.495	15.010	14.822	
16.000	84.00	HCQ-125	1910	6770	6770		6770	1773		2809	3014	0.495	15.010	14.822	
16.000	84.00	Q-125	1480	6770	6770		6770	1773		2809	3014	0.495	15.010	14.822	
16.000	95.00	N-80	2180	4950			4950			2161	2196	0.566	14.868		14.750
16.000	95.00	HCN-80	2580	4950			4950			2161	2196	0.566	14.868		14.750
16.000	95.00	HCP-110	2580	6810			6810			2866	3019	0.566	14.868		14.750
16.000	95.00	P-110	2230	6810			6810			2866	3019	0.566	14.868		14.750
16.000	95.00	HCQ-125	2580	7740			7740			3198	3431	0.566	14.868		14.750
16.000	95.00	Q-125	2230	7740			7740			3198	3431	0.566	14.868		14.750
16.000	97.00	N-80	2270	5030			5030			2194	2230	0.575	14.850		14.750
16.000	97.00	HCN-80	2990	5030			5030			2194	2230	0.575	14.850		14.750
16.000	97.00	HCP-110	2990	6920			6920			2910	3067	0.575	14.850		14.750
16.000	97.00	P-110	2340	6920			6920			2910	3067	0.575	14.850		14.750
16.000	97.00	HCQ-125	2990	7860			7860			3246	3485	0.575	14.850		14.750
16.000	97.00	Q-125	2340	7860			7860			3246	3485	0.575	14.850		14.750
16.000	109.00	J-55	2560	3950	3950		3950	1116		1772	1739	0.656	14.688	14.500	
16.000	109.00	K-55	2560	3950	3950		3950	1181		1965	1739	0.656	14.688	14.500	
16.000	109.00	N-80	3080	5740	5740		5740	1594		2489	1739	0.656	14.688	14.500	
16.000	118.00	J-55	3170	4300	4300		4300	1224		1924	1889	0.715	14.570	14.382	
16.000	118.00	K-55	3170	4300	4300		4300	1296		2131	1889	0.715	14.570	14.382	
16.000	118.00	N-80	3680	6260	6260		6260	1741		2703	2747	0.715	14.570	14.382	