

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	SD
				PE	STC	LTC	BTC	STC	LTC	BTC				API	
18.625	87.50	H-40	630	1630	1630		1630	559		993	995	0.435	17.755	17.567	
18.625	87.50	J-55	630	2250	2250		2250	754		1329	1368	0.435	17.755	17.567	
18.625	87.50	K-55	630	2250	2250		2250	794		1427	1368	0.435	17.755	17.567	
18.625	87.50	N-80	630	3270	3270		3270	1079		1887	1990	0.435	17.755	17.567	
18.625	94.50	H-40	780	1760	1760		1760	609		1067	1068	0.468	17.689	17.501	
18.625	94.50	J-55	780	2420	2420		2420	821		1427	1469	0.468	17.689	17.501	
18.625	94.50	K-55	780	2420	2420		2420	865		1533	1469	0.468	17.689	17.501	
18.625	94.50	N-80	780	3520	3520		3520	1174		2027	2137	0.468	17.689	17.501	
18.625	106.00	H-40	1140	2000	2000		2000	703		1206	1208	0.531	17.563	17.375	
18.625	106.00	J-55	1140	2740	2740		2740	948		1613	1661	0.531	17.563	17.375	
18.625	106.00	K-55	1140	2740	2740		2740	998		1733	1661	0.531	17.563	17.375	
18.625	106.00	N-80	1150	3990	3990		3990	1356		2292	2416	0.531	17.563	17.375	
18.625	117.50	H-40	1500	2230	2230		2230	795		1342	1344	0.593	17.439	17.251	
18.625	117.50	J-55	1510	3060	3060		3060	1072		1795	1849	0.593	17.439	17.251	
18.625	117.50	K-55	1510	3060	3060		3060	1129		1929	1849	0.593	17.439	17.251	
18.625	117.50	N-80	1620	4460	4460		4460	1534		2551	2689	0.593	17.439	17.251	