

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	
				PE	STC	LTC	BTC	STC	LTC	BTC				API	SD
5.750	16.50	J-55	3720	4620			4620			314	234	0.276	5.198		5.073
5.750	18.10	J-55	4520	5090			5090			344	286	0.304	5.142		5.017
5.750	18.10	L-80	5700	7400			7400			447	416	0.304	5.142		5.017
5.750	18.10	N-80	5700	7400			7400			466	416	0.304	5.142		5.017
5.750	18.10	C-95	6380	8790			8790			502	494	0.304	5.142		5.017
5.750	18.10	P-110	6640	10180			10180			594	572	0.304	5.142		5.017
5.750	19.70	J-55	5410	5610			5610			377	313	0.335	5.080		4.955
5.750	19.70	L-80	7030	8160			8160			490	456	0.335	5.080		4.955
5.750	19.70	N-80	7030	8160			8160			511	456	0.335	5.080		4.955
5.750	19.70	C-95	7980	9690			9690			550	541	0.335	5.080		4.955
5.750	19.70	P-110	8530	11220			11220			651	627	0.335	5.080		4.955
5.750	21.80	L-80	8740	9130			9130			545	507	0.375	5.000		4.875
5.750	21.80	N-80	8740	9130			9130			568	507	0.375	5.000		4.875
5.750	21.80	C-95	10050	10840			10840			611	602	0.375	5.000		4.875
5.750	21.80	P-110	10960	12550			12550			723	697	0.375	5.000		4.875
5.750	24.20	L-80	10650	10230			10230			605	563	0.420	4.910		4.785
5.750	24.20	N-80	10650	10230			10230			630	563	0.420	4.910		4.785
5.750	24.20	C-95	12370	12140			12140			679	668	0.420	4.910		4.785
5.750	24.20	P-110	13700	14060			14060			803	774	0.420	4.910		4.785