

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	
				PE	STC	LTC	BTC	STC	LTC	BTC				API	SD
7.750	46.10	L-80	11340	10750		10490	9790		841	1001	1070	0.595	6.560	6.435	6.500
7.750	46.10	HCL-80	13320	10750		10490	9790		965	1091	1070	0.595	6.560	6.435	6.500
7.750	46.10	C-90	12740	12090		11810	11010		928	1074	1204	0.595	6.560	6.435	6.500
7.750	46.10	H2S-90	12740	12090		11810	11010		965	1091	1204	0.595	6.560	6.435	6.500
7.750	46.10	S-95	13320	12760		12460	11620		992	1168	1271	0.595	6.560	6.435	6.500
7.750	46.10	T-95	13320	12760		12460	11620		978	1129	1271	0.595	6.560	6.435	6.500
7.750	46.10	H2S-95	13320	12760		12460	11620		978	1129	1271	0.595	6.560	6.435	6.500
7.750	46.10	C-95	13320	12760		12460	11620		978	1129	1271	0.595	6.560	6.435	6.500
7.750	46.10	P-110	14990	14780		14430	13460		1142	1334	1471	0.595	6.560	6.435	6.500
7.750	46.10	Q-125	16580	16790		16400	15290		1279	1462	1672	0.595	6.560	6.435	6.500