

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	
				PE	STC	LTC	BTC	STC	LTC	BTC				API	SD
8.625	24.00	J-55	1370	2950	2950			244			381	0.264	8.097	7.972	
8.625	24.00	K-55	1370	2950	2950			263			381	0.264	8.097	7.972	
8.625	24.00	HCK-55	1780	2950	2950			326			381	0.264	8.097	7.972	
8.625	28.00	H-40	1610	2470	2470			233			318	0.304	8.017	7.892	
8.625	28.00	HCK-55	2680	3390	3390	3390	3390	414	464	651	437	0.304	8.017	7.892	
8.625	32.00	H-40	2200	2860	2860			279			366	0.352	7.921	7.796	7.875
8.625	32.00	J-55	2530	3930	3930	3930	3930	372	417	579	503	0.352	7.921	7.796	7.875
8.625	32.00	K-55	2530	3930	3930	3930	3930	402	452	690	503	0.352	7.921	7.796	7.875
8.625	32.00	HCK-55	4130	3930	3930	3930	3930	497	556	749	503	0.352	7.921	7.796	7.875
8.625	36.00	J-55	3450	4460	4460	4460	4460	434	486	654	568	0.400	7.825	7.700	
8.625	36.00	K-55	3450	4460	4460	4460	4460	468	526	780	568	0.400	7.825	7.700	
8.625	36.00	HCK-55	5300	4460	4460	4460	4460	579	648	847	568	0.400	7.825	7.700	
8.625	36.00	L-80	4100	6490		6490	6490		678	864	827	0.400	7.825	7.700	
8.625	36.00	HCL-80	6060	6490		6490	6490		779	945	827	0.400	7.825	7.700	
8.625	36.00	N-80	4100	6490		6490	6490		688	895	827	0.400	7.825	7.700	
8.625	36.00	HCN-80	6060	6490		6490	6490		779	945	827	0.400	7.825	7.700	
8.625	40.00	L-80	5520	7300		7300	7300		776	966	925	0.450	7.725	7.600	7.625
8.625	40.00	HCL-80	7900	7300		7300	7300		892	1057	925	0.450	7.725	7.600	7.625
8.625	40.00	N-80	5520	7300		7300	7300		788	1001	925	0.450	7.725	7.600	7.625
8.625	40.00	HCN-80	7900	7300		7300	7300		892	1057	925	0.450	7.725	7.600	7.625
8.625	40.00	C-90	5870	8220		8220	8220		858	1038	1040	0.450	7.725	7.600	7.625
8.625	40.00	H2S-90	7900	8220		8220	8220		892	1057	1040	0.450	7.725	7.600	7.625
8.625	40.00	S-95	7900	8670		8670	8670		915	1127	1098	0.450	7.725	7.600	7.625
8.625	40.00	T-95	6020	8670		8670	8670		904	1092	1098	0.450	7.725	7.600	7.625
8.625	40.00	H2S-95	7900	8670		8670	8670		904	1092	1098	0.450	7.725	7.600	7.625
8.625	40.00	C-95	6020	8670		8670	8670		904	1092	1098	0.450	7.725	7.600	7.625
8.625	40.00	HCP-110	7900	10040		10040	10040		1055	1228	1271	0.450	7.725	7.600	7.625
8.625	40.00	P-110	6390	10040		10040	10040		1055	1228	1271	0.450	7.725	7.600	7.625
8.625	49.00	L-80	8580	9040		9040	9040		983	1180	1129	0.557	7.511	7.386	
8.625	49.00	HCL-80	10400	9040		9040	9040		1129	1291	1129	0.557	7.511	7.386	
8.625	49.00	N-80	8580	9040		9040	9040		997	1222	1129	0.557	7.511	7.386	
8.625	49.00	HCN-80	10400	9040		9040	9040		1129	1291	1129	0.557	7.511	7.386	
8.625	49.00	C-90	9340	10170		10170	10170		1085	1268	1271	0.557	7.511	7.386	
8.625	49.00	H2S-90	10400	10170		10170	10170		1129	1291	1271	0.557	7.511	7.386	
8.625	49.00	S-95	10400	10740		10740	10740		1159	1377	1341	0.557	7.511	7.386	
8.625	49.00	T-95	9710	10740		10740	10740		1144	1334	1341	0.557	7.511	7.386	
8.625	49.00	H2S-95	10400	10740		10740	10740		1144	1334	1341	0.557	7.511	7.386	
8.625	49.00	C-95	9710	10740		10740	10740		1144	1334	1341	0.557	7.511	7.386	
8.625	49.00	P-110	10740	12430		12430	12430		1335	1574	1553	0.557	7.511	7.386	
8.625	49.00	Q-125	11650	14130		14130	14130		1496	1728	1765	0.557	7.511	7.386	
8.625	49.00	V-150	12950	16950		16950	16950		1789	2056	2118	0.557	7.511	7.386	
8.625	44.00	L-80	6950	8120		8120	8120		874	1066	1021	5.000	7.625	7.500	
8.625	44.00	HCL-80	9100	8120		8120	8120		1004	1167	1021	5.000	7.625	7.500	
8.625	44.00	N-80	6950	8120		8120	8120		887	1105	1021	5.000	7.625	7.500	

O.D. (INCH)	NOMINAL WEIGHT (T&C LBS/FT)	GRADE	COLLAPSE (PSI)	INTERNAL YEILD PRESSURE AT MINIMUM YIELD (PSI)				JOINT STRENGTH 1000 LBS			BODY YIELD 1000 LBS	WALL (IN)	LD (INCH)	DRIFT DIAMETER (INCH)	
				PE	STC	LTC	BTC	STC	LTC	BTC				API	SD
8.625	44.00	HCN-80	9100	8120		8120	8120		1004	1167	1021	5.000	7.625	7.500	
8.625	44.00	C-90	7490	9130		9130	9130		965	1146	1149	5.000	7.625	7.500	
8.625	44.00	H25-90	9100	9130		9130	9130		1004	1167	1149	5.000	7.625	7.500	
8.625	44.00	S-95	9100	9640		9640	9640		1030	1244	1212	5.000	7.625	7.500	
8.625	44.00	T-95	7740	9640		9640	9640		1017	1206	1212	5.000	7.625	7.500	
8.625	44.00	H25-95	9100	9640		9640	9640		1017	1206	1212	5.000	7.625	7.500	
8.625	44.00	C-95	7740	9640		9640	9640		1017	1206	1212	5.000	7.625	7.500	
8.625	44.00	HCP-110	9100	11160		11160	11160		1186	1423	1404	5.000	7.625	7.500	
8.625	44.00	P-110	8420	11160		11160	11160		1186	1423	1404	5.000	7.625	7.500	
8.625	44.00	HCQ-125	9100	12680		12680	12680		1330	1562	1595	5.000	7.625	7.500	
8.625	44.00	Q-125	8980	12680		12680	12680		1330	1562	1595	5.000	7.625	7.500	
8.625	44.00	V-150	9640	15220		15220	15220		1591	1859	1914	5.000	7.625	7.500	